



# VALUE WITHOUT COMPROMISE

Introducing the solid industrial tyre from Barum. The Barum INDUSTRY has great performance for general use on forklifts and other industrial vehicles. And because it is a solid tyre, it's damage resistant and maintenance-free.

## BARUM INDUSTRY



## BARUM INDUSTRY CLEAN



# BARUM

## INDUSTRY

### Features:

Thick sidewall layer protects the tyre construction and offers additional impact resistance for demanding applications



Central tread rib improves straightline stability and steering response



Offset tread pattern provides a smooth ride and even wear



### Technical specifications:

Tyre size		Rim size	Load Capacity(kg) Forklift Trucks max.25km/h (16mph)		Nominal Dimensions (mm)	
			Load	Steer	Width ±2%	Diameter ±1%
4.00 - 8*		3.00 D-8	950	730	101	398
5.00 - 8*		3.00 D-8	1415	1090	120	448
125/75 - 8*	15x4½ - 8	3.00 D-8	1040	800	115	368
150/75 - 8*	16x6 - 8	4.33 R-8	1495	1150	145	408
180/70 - 8*	18x7 - 8	4.33 R-8	2145	1650	146	445
6.00 - 9*		4.00 E-9	1885	1450	135	519
200/75 - 9*	21x8 - 9	6.00 E-9	2755	2120	177	512
6.50 - 10*		5.00 F-10	2340	1800	158	563
200/50 - 10*		6.50 F-10	2470	1900	190	448
225/75 - 10*	23x9 - 10	6.50 F-10	3445	2650	190	572
7.00 - 12*		5.00 S-12	2920	2240	166	645
250/60 - 12*	23x10 - 12	8.00 G-12	3770	2900	230	569
250/75 - 12*	27x10 - 12	8.00 G-12	3900	3000	225	663
8.25 - 15*		6.5 - 15	4750	3650	198	805
225/75 - 15	28x9 - 15	7.0 - 15	3900	3000	206	680
250/70 - 15	250 - 15	7.0 - 15	4750	3650	207	706
315/70 - 15	300 - 15	8.0 - 15	5850	4500	237	809
355/65 - 15		9.75 - 15	7800	6000	277	809

All dimensions can be delivered in SIT and standard rim versions.  
\* also available as Clean.